Repair and Maintenance Switch ALU-Enclosure with ALU-Lock Ring





Aluminium Diecast-Housing with Aluminium Lock Ring Gr.1 (AL-2/AL-3)

Repair and Maintenance Switch

- as **main switch** in the aluminum housing in the Version: handle / front: black / black = sw / sw
- as an **emergency stop switch** in the aluminum housing in the Version: handle / front: red / yellow =

Compact Switch (ML0/ML1)

Cam Switch (MN105 / MN151 / MN251)



Aluminium-Lock Ring with lockout handle for 3 padlocks

with bracket diameter up to 9 mm,

Housing: for indoor / outdoor use High degree of protection: IP 65

Extremely robust and impact-resistant, delivery ready for assembly with 2 locking screws without cable glands. Painting according to customer possible (standard: natural aluminum)

Specifications

Compact Switches	ML0-016	ML0-032	ML1-025	ML1-040
Rated operating current I _e	25 A	32 A	25 A	40 A
Rated voltage U _e	690 V	690 V	690 V	690 V
Rated uniterrupted current I = I th (open)	25 A	32 A	25 A	40 A
Conventional enclosed thermal current I _{the}	25 A	32 A	25 A	40 A

Cam Switches	MN105	MN151	MN251
Rated operational current I _e	25 A	32 A	40 A
Rated operational voltage U _e	690 V	690 V	690 V
Rated uninterrupted current I _{th}	25 A	32 A	40 A
Rated uninterrupted current I _{the}	25 A	32 A	40 A



Advantages:

- Mechanically extremely robust.
- Ideally suited for harsh environments.
- Significantly higher security against manipulation compared to plastic.
- Wherever the usual lock rings cannot be used or can only be used with reservations due to mechanical or physical conditions.
- More resistant to aging than plastic, especially where extreme heat or cold clog the housing or locking ring.
- Optionally available in EMC Version

Application areas:

Areas with harsh conditions such as:

- Conveyor technology
- Logistics in all areas such as:
 - Airport logistics, shipping
 - Quarries, mining, tunneling
 - Storage and shipping logistics
 - Mechanical engineering, sawmills
 - Processing plants
 - Forestry and Agriculture

Can be used for all outdoor areas!



Fax +49 (0) 7971 252-351