

Repair and Maintenance Switch UL-certified incl. M15 Power LQ-System



Outdoor
Type Rating 4X



Indoor
Type Rating 12



We make it simple.



Switch to Quality!

This complete solution can be used in the most extreme environmental conditions.
 IP66 withstands strong splash water and can be used under water for a defined time.
Outdoor Type Rating 4X - Indoor Type Rating 12

Switch disconnecter in enclosure 996X

Technical Specifications

- Material: Polycarbonate
- Color: Grey
- RAL number: 7035

Mechanical properties

- Impact resistance: IK 08
- ETIM Class: EC000261

Ratings

- Degree of protection: IP66, EV006423
- Flammability class: f1 approved UL 746C
5 inch flame test

Temperatures

- Ambient temperature: -30 ... 80 °C
- Short term temperature range: -30 ... 120 °C

M15 Power - Connector with cable

- 4-pole: 3-pole + PE
- 6-pole: 3-pole + 2-pole + PE



CONVEYING TECHNIQUES



INTRA-LOGISTICS



LOGISTICS



AIR CONDITIONING / VENTILATION



We help you finding the right switch for your project! Contact us.



We make it simple.

LQ Mechatronik-Systeme GmbH

Carl-Benz-Straße 6 Telefon +49 (0) 7143 968-0
 D-74354 Besigheim Fax +49 (0) 7143 968-399

info@de.lq-group.com
 www.lq-group.com/de/



Switch to Quality!

MERZ Schaltgeräte GMBH + CO KG

Kernerstraße 15 Telefon +49 (0) 7971 252-252
 D-74405 Gaildorf Fax +49 (0) 7971 252-351

info@merz-schaltgeraete.de
 www.merz-schaltgeraete.de