


Technical data MDC10-040-1000-3

acc. IEC 60947-1, IEC 60947-3, CCC			
Rated insulation Voltage		Vdc	1000
Conventional thermal current I_{th}	open	Adc	50
Rated impulse withstand voltage U_{imp}		kV	8
Rating			
Rated operational voltage U_e	DC-21B	Vdc	-
Rated operational current I_e		Adc	-
Rated operational voltage U_e	DC-21B	Vdc	-
Rated operational current I_e		Adc	-
Rated operational voltage U_e	DC-PV1	Vdc	400
Rated operational current I_e		Adc	50
Rated operational voltage U_e	DC-PV1	Vdc	600
Rated operational current I_e		Adc	45
Rated operational voltage U_e	DC-PV1	Vdc	800
Rated operational current I_e		Adc	32
Rated operational voltage U_e	DC-PV1	Vdc	1000
Rated operational current I_e		Adc	25
Rated operational voltage U_e	DC-PV2	Vdc	400
Rated operational current I_e		Adc	20
Rated operational voltage U_e	DC-PV2	Vdc	600
Rated operational current I_e		Adc	16
Rated operational voltage U_e	DC-PV2	Vdc	800
Rated operational current I_e		Adc	12
Rated operational voltage U_e	DC-PV2	Vdc	1000
Rated operational current I_e		Adc	7
Rated short time withstand current $I_{cw, 1sec}$		Adc	600
Rated short time making capacity I_{cm}		Adc	600
Cross-section		AWG	14 - 6
Pollution degree			3
Overvoltage category			III
Terminal cross section solid or multi-stranded	min./max.	mm ²	1,5 - 16
Finely stranded with ferrule	min./max.	mm ²	1,5 - 16
Terminal screws			M4
Torque terminal screws		Nm	1,2 - 1,4
Ambient temperature		C°	+75/-25
Ambient temperature peaks up to		C°	+75

Available for 1, 2 and 3MPPT



Subject to change without notice, errors and errata excepted.