

MDC10/MDC40

*** nur mit Ring-Kabelschuh, Querschnitt passend zum Strom / *only with ring cable lug, cross-section suitable for the current*

MDC-10 040 1000 2	MDC-10 040 1000 21	MDC-10 040 1000 41	MDC-10 040 1000 32	MDC-10 040 1000 4	MDC-10 040 1000 42	MDC-10 040 1000 62	MDC-10 040 1000 63	MDC-40 160 1000 4
1	1	1	2	2	2	2	3	1
1200*/1100	1500	1500	1100	1500	1500	1500	1200	1000
50	50	50	50	50	50	50	50	160
8	8	8	8	8	8	8	8	8
400	400	400	400	400	400	400	400	400
50	50	50	25 (50)	50	50	50	50	160
600	600	600	600	600	600	600	600	600
45	50	50	20 (40)	36	36	50	36	160
800	800	800	850	800	800	800	800	800
32	25	50	12 (24)	25	25	50	22	160
1000	1000	1000	1000	1000	1000	1000	1000	1000
20	* 20/16	50	8 (16)	16	* 20/16	50	16	160
1200	1200		1100	1200	1200	1200	1200	
8	10		7 (14)	10	10	26	8	
	1500	1500		1500	1500	1500		
	5	32		5	5	20		
400	400	400	280		400			
18,75	18	50	25		18			
600	600	600	400		600	550		
16,8	15	40	18		15	30		
800	800	800	500		800	800		
12	12	30	14		12	20		
1000	1000	1000	600		1000	1000		1000
7,5	9	25	12		9	18		160
		1500						
		15						
600	600	600	600	600	600	600	600	2000
600	600	600	600	600	600	600	600	2000
1,5 - 10	1,5 - 10	1,5 - 10	1,5 - 10	1,5 - 10	1,5 - 10	1,5 - 10	1,5 - 10	** Kabelschuh + Schraube / Cable lug + Screw bis / up to 70 +40/-5 max +90 3,0
1,5 - 10	1,5 - 10	1,5 - 10	1,5 - 10	1,5 - 10	1,5 - 10	1,5 - 10	1,5 - 10	
+75/-25	+75/-25	+75/-25	+75/-25	+75/-25	+75/-25	+75/-25	+75/-25	
1,2 - 1,4	1,2 - 1,4	1,2 - 1,4	1,2 - 1,4	1,2 - 1,4	1,2 - 1,4	1,2 - 1,4	1,2 - 1,4	
					600		600	
					30		30	
					800		800	
					24		24	
					1000		1000	
					10		10	
					5		5	
					40A / 1000V		40A / 1000V	
					14 - 8 / 105°		14 - 8 / 105°	
					+75		+75	
					1,2 - 1,4		1,2 - 1,4	
3	3	3	3	3	3	3	3	3
III	III	III	III	III	III	III	III	III
Cu	Cu	Cu	Cu	Cu	Cu	Cu	Cu	Cu
12	12	12	12	12	12	12	12	nach Vereinbarung / by arrangement
M4	M4	M4	M4	M4	M4	M4	M4	M6

* 16A nach CQC-Zertifikat (20A bestätigt nach interner Prüfung gemäß PB190416-01 el. Lebensdauer, PB190617-04 Ein-Ausschaltvermögen

* 16A according to CQC certificate (20A confirmed after internal test PB190416-01 el. Service life, PB190617-04 on-breaking capacity