

Technical_data_ML2-063

Version: 01/01/2021

Page 1/1

Technical data ML2-063

acc. IEC 60947-3, EN 60947-3			
Rated operational current I_e	AC 21 A	A	63
Rated operational voltage U_e		V	690
Rated uninterrupted current I_{th}	open	A	63
Rated uninterrupted current I_{the}	encapsulated	A	63
Rated insulation voltage U_i Insulation group C acc. VDE 0110		V	690
Rated impulse withstand voltage U_{imp} (III/3)		kV	6
Making/breaking capacity	Utilisation category		
	AC 3		
	230 V 3~	kW	15
	430 V 3~	kW	22
	690 V 3~	kW	22
Making/breaking capacity	Utilisation category		
	AC 23B		
	230 V 3~	kW	18,5
	430 V 3~	kW	30
	690 V 3~	kW	30
Making/breaking capacity	Utilisation category		
	AC 22A		
	230 V 3~	A	63
	430 V 3~	A	63
	690 V 3~	A	63
Short-circuit capacity			
Max. fuse rating (gG-Char.)		A	63
Rated conditional short-circuit current	4-pol. / 3-pol.	kA	10
Isolating characteristic up to		V~	690
Terminal cross section solid or multi-stranded	min./max.	mm ²	2,5 - 35
finely stranded with ferrule	min./max.	mm ²	1,5 - 25
Terminal screws			M5
Torque terminal screws		Nm	2
Mechanical life	operating cycles		30.000
Ambient temperature max./min.	open	C°	+50/-25
	encapsulated	C°	+40/-25
acc. UL und CSA			
Rated operational current		A	63
Rated operational voltage		V	600
Making/breaking capacity	Utilisation category		
	AC 3		
Motor 3-phase	220/240 V 3~	hp	15
	440/480 V 3~	hp	30
	550/600 V 3~	hp	30
Making/breaking capacity	Utilisation category		
	AC 3		
Motor 1-phase	110/120 V	hp	3
	220/240 V	hp	7,5
Cable cross section		AWG-No	14 - 2

Subject to change without notice, errors and errata excepted.