

Technical_data_UVR_MN_451

Version: 01/01/2021

Page 1/1

Technical data UVR MN 451

CE marking acc. IEC 947-3, EN 60947-3			
Rated operational current I_e	AC 21 A	A	50
Rated operational voltage U_e		V	690
Rated uninterrupted current I_{th}	open	A	63
Rated uninterrupted current I_{the}	encapsulated	A	63
Rated insulation voltage U_i Insulation group C acc. VDE 0110		V	690
Rated impulse withstand voltage U_{imp} (III/3)		kV	6
Making/breaking capacity	Utilisation category		
	AC 3		
	230 V 3~	kW	11
	430 V 3~	kW	18,5
	690 V 3~	kW	22
Single-phase motor	230 V	kW	5,5
	430 V	kW	7,5
Making/breaking capacity	Utilisation category		
	AC 23A(B)		
	230 V 3~	kW	15
	430 V 3~	kW	22
	690 V 3~	kW	30
Short-circuit capacity			
Max. fuse rating (gG-Char.)		A	63
Rated conditional short-circuit current		kA _{eff}	6
Rated short-time withstand current I_{cw1sec}		A	600
Rated short circuit making capacity I_{cm}		A	-
Isolating characteristics up to		V~	690
Terminal cross section solid or multi-stranded	min./max.	mm ²	1,0 - 10
Finely stranded with ferrule	min./max.	mm ²	1,0 - 10,0
Terminal screws			M5
Torque terminal screws		Nm	2,2
Mechanical life	Operating cycles		1x10 ⁶
Ambient temperature	open	C°	+50/-25
	encapsulated	C°	+40/-25
Under voltage release			
Pick-up		% of U_e	≥ 85
Drop-out		% of U_e	35 ... 75
Operation continues		% of U_e	100

Subject to change without notice, errors and errata excepted.